


MIL-W-22759/4 | SAE AS22759/4
MIL-W-22759/4 Wire (M22759/4 Wire)
SAE AS22759/4
MIL Spec Wire
600V, 200° C



MIL-W-22759/4 Wire (M22759/4 Wire) Description:

Conductor: Silver Plated Copper
Insulation: PTFE, FEP, and Glass
MIL-W-22759/4 Wire (M22759/4 Wire) Characteristics:

Voltage Rating: 600 Volts
Temperature Rating: 200° C
MIL-W-22759/4 Wire (M22759/4 Wire) Common Applications:

Durable M22759 MIL-Spec Wire may be used in aircraft engines and in other military, government, or civilian applications where abrasion is present.
Customization Services for MIL-W-22759/4 include:

Part Number	AWG Size	Conductor Stranding	Approx LBS/MFT	Min O.D. (in)	Max O.D. (in)
M22759/4-22	22	19/34	5.9	0.071	0.077
M22759/4-20	20	19/32	7.9	0.079	0.085
M22759/4-18	18	19/30	11	0.092	0.098
M22759/4-16	16	19/29	13.6	0.99	0.998
M22759/4-14	14	19/27	18.5	0.112	0.12
M22759/4-12	12	37/28	26.6	0.129	0.137
M22759/4-10	10	37/26	41.5	0.159	0.171
M22759/4-8	8	133/29	77.4	0.228	0.242
M22759/4-6	6	133/27	115	0.272	0.292
M22759/4-4	4	133/25	184	0.336	0.366
M22759/4-2	2	665/30	281	0.415	0.445
M22759/4-1	1	817/30	358	0.465	0.495
M22759/4-01	1/0	1045/30	436	0.5	0.55
M22759/4-02	2/0	1330/30	554	0.56	0.61