

MIL-C-76 Type LWP
MIL-C-76
MIL Spec Wire



MIL-C-76 Type LWP Cable Construction:

Conductor: Stranded or Solid Tinned Copper
Insulation: Polyvinyl Chloride (PVC), Color Coded
MIL-C-76 Type LWP Cable Ratings:

Voltage Rating: 300 volts
Temperature Rating: -55° C to +90° C

Part Number	AWG Size	Nom. O.D. (in)	Nom. Dia. of Cond.	Conductor Stranding	Nom. Insul. Thick. (in)	Mil-Spec #
M76-LWP-30-1	30	0.030	0.010	Solid	0.010	M76LWPC301A
M76-LWP-30-7/38	30	0.032	0.012	7/38	0.010	M76LWPC307A
M76-LWP-28-1	28	0.033	0.013	Solid	0.010	M76LWPC281A
M76-LWP-28-7/36	28	0.035	0.015	7/36	0.010	M76LWPC287A
M76-LWP-26-1	26	0.036	0.016	Solid	0.010	M76LWPC261A
M76-LWP-26-7/26	26	0.039	0.019	7/34	0.010	M76LWPC267A
M76-LWP-24-1	24	0.040	0.020	Solid	0.010	M76LWPC241A
M76-LWP-24-7/32	24	0.044	0.024	7/32	0.010	M76LWPC247A
M76-LWP-22-1	22	0.045	0.025	Solid	0.010	M76LWPC221A
M76-LWP-22-7/30	22	0.050	0.030	7/30	0.010	M76LWPC227A
M76-LWP-20-1	20	0.052	0.032	Solid	0.010	M76LWPC201A
M76-LWP-20-7/28	20	0.058	0.038	7/28	0.010	M76LWPC207A