

MIL-C-76 Type HWP
MIL-C-76 Type HWP
MIL Spec Wire



MIL-C-76 Type HWP Cable Construction:

Conductor: Stranded Tinned Copper
Insulation: PVC, Color Coded
MIL-C-76 Type HWP Cable Ratings:

Voltage Rating: 2,500 Volts (22-16 AWG), 600 Volts (14 AWG and larger)
Temperature Rating: -55° C to +90° C

Part Number	AWG Size	Nom. O.D. (in)	Conductor Stranding	Nom. Dia. of Cond.	Nom. Insul. Thick. (in)	Mil-Spec #
M76-HWP-22	22	0.092	7/30	0.030	0.031	M76HWPC227A
M76-HWP-20	20	0.099	10/30	0.037	0.031	M76HWPC2010A
M76-HWP-18	18	0.107	16/30	0.045	0.031	M76HWPC1816A
M76-HWP-16	16	0.120	19/29	0.059	0.031	M76HWPC1619A
M76-HWP-14	14	0.163	19/27	0.073	0.045	M76HWPC1419A
M76-HWP-12	12	0.182	19/25	0.092	0.045	M76HWPC1219A
M76-HWP-10	10	0.205	37/26	0.115	0.045	M76HWPC1037A
M76-HWP-8	8	0.258	133/29	0.166	0.045	M76HWPC8133A
M76-HWP-6	6	0.300	133/27	0.210	0.045	M76HWP6133A