

MIL-C-76 Type MWP Glass Braid
MIL-C-76 Type MWP Glass Braid
MIL Spec Wire

MIL-C-76 Type MWP Glass Braid Construction:

Conductor: Stranded or Solid Tinned Copper
Insulation: PVC with Lacquered Glass Braid Overall
MIL-C-76 Type MWP Glass Braid Ratings:

Voltage Rating: 1,000 volts
Temperature Rating: -55° C to +80° C

Part Number	AWG Size	nductor Strandi	Nom. O.D. (in)	Nom. Dia. of Cond.	Nom. Insul. Thick. (in)	Mil-Spec #
M76-MWP-24-GB	24	7/32	0.066	0.024	0.016	M76MWPC247C
M76-MWP-22-GB	22	7/30	0.072	0.030	0.016	M76MWPC227C
M76-MWP-20-GB	20	10/30	0.079	0.037	0.016	M76MWPC2010C
M76-MWP-18-GB	18	16/30	0.087	0.045	0.016	M76MWPC1816C
M76-MWP-16-GB	16	19/29	0.098	0.056	0.016	M76MWPC1619C
M76-MWP-14-GB	14	19/27	0.113	0.071	0.016	M76MWPC1419C
M76-MWP-12-GB	12	19/25	0.132	0.090	0.016	M76MWPC1219C

