

MIL-C-76 Type MWP Tinned Copper Braid

MIL-C-76 Type MWP Tinned Copper Braid
MIL Spec Wire

MIL-C-76 Type MWP Tinned Copper Braid Construction:

Conductor: Stranded Tinned Copper
Insulation: Polyvinyl Chloride (PVC)
Shield: Braided Tinned Copper
MIL-C-76 Type MWP Tinned Copper Braid Ratings:

Voltage Rating: 1,000 volts
Temperature Rating: -55° C to +80° C

Part Number	AWG Size	Conductor Stranding	Nom. O.D. (in)	Nom. Dia. of Cond.	Nom. Insul. Thick. (in)	Mil-Spec #
M76-MWP-24-TCBS	24	7/32	0.078	0.024	0.016	M76MWPC247D
M76-MWP-22-TCBS	22	7/30	0.084	0.030	0.016	M76MWPC227D
M76-MWP-20-TCBS	20	10/30	0.091	0.037	0.016	M76MWPC2010D
M76-MWP-18-TCBS	18	16/30	0.099	0.045	0.016	M76MWPC1816D
M76-MWP-16-TCBS	16	19/29	0.110	0.056	0.016	M76MWPC1619D
M76-MWP-14-TCBS	14	19/27	0.125	0.071	0.016	M76MWPC1419D
M76-MWP-12-TCBS	12	19/25	0.144	0.090	0.016	M76MWPC1219D

