

MIL-C-915/1 (CVSF)
MIL-C-915/1 Power and Lighting Cable
CVSF

MIL-C-915/1 Construction:

Conductor: 1 Uninsulated and 3 Insulated Bare Copper Conductors
Insulation: Rubber
Jacket: Neoprene
MIL-C-915/1 Approvals and Ratings:

M915E
Navy Spec CVSF
Voltage Rating: 600 Volts
MIL-C-915/1 Applications:



This cable may be used in special purpose power, lighting, and shipboard applications.
MIL-C-915/1 Description:

Special purpose
Non-watertight cable
Flexing Cable

Part Number	Approx LBS/MFT	Composite Construction	Max O.D. (in)
CVSF-4	1300	(1) 5 AWG Uninsulated Conductor and (3) 3 AWG Insulated Conductors	1.450

Part Number: CVSF-4			
MIL-C-915/1 (CVSF)			
CVSF-4 Specifications: (subject to change without notice)			
Approx LBS/MFT	1300		
Composite Construction	(1) 5 AWG Uninsulated Conductor and (3) 3 AWG Insulated Conductors		
Max O.D. (in)	1.450		
Mil-Spec	M915E/1		
Ampacity (Cond.) @ 50°	75		
Metal Tubes	N		
Nylon Tubes	7C		
Cond. Material	Bare Copper		
Insul. Material	Rubber		
Jacket Material	Neoprene		
Voltage	600		