

MIL-C-915/7 (DSWS)
MIL-C-915/7 Power and Lighting Cable
DSWS

MIL-C-915/7 Approvals and Ratings:

MIL-C-915E, M915
Navy Spec DSWS
Service: 600 Volts
MIL-C-915/7 Construction:

Conductor: 2 Tinned Copper Conductors
Insulation: Rubber
Jacket: Neoprene
Shield: Overall Tinned Copper Braid
Unarmored with surface marking
MIL-C-915/7 Description:

Power and Lighting Cable
Watertight Cable

Non-Flexing Cable

Part Number	AWG Size	No. of Cond.	Approx LBS/MFT	Max O.D. (in)
DSWS-4	14	2	50	0.800
Part Number: DSWS-4				
MIL-C-915/7 (DSWS)				
DSWS-4 Specifications: (subject to change without notice)				
AWG Size	14			
No. of Cond.	2			
Approx LBS/MFT	50			
Max O.D. (in)	0.800			
Mil-Spec	M915E/7			
Metal Tubes	E			
Nylon Tubes	5A			
Cond. Material	Tinned Copper			
Jacket Material	Neoprene			
Insul. Material	Rubber			
Shield	Overall Braid Shield			
Shield Material	Tinned Copper Braid			
Voltage	600			

