

MIL-C-915/21 (TRXF)
MIL-C-915/21 Welding Cable (TRXF)

MIL-C-915/21 Welding Cable (TRXF) Construction:

Conductor: Single ultra flexible bare copper conductor
Suitable separator
Sheath: Polychloroprene
MIL-C-915/21 Welding Cable (TRXF) Description:



M915/21 cable is an unarmored, non-watertight cable that meets MIL-C-915E. It is very flexible cable with 600 volt service.

Part Number	AWG Size	No. of Cond.	Approx LBS/MFT	Max O.D. (in)
TRXF-84	1	1	360	0.600
TRXF-105	1/0	1	460	0.680
TRXF-133	2/0	1	567	0.750

Part Number: TRXF-84
MIL-C-915/21 (TRXF)

Dimensions: (subject to change without notice)

AWG Size	1
No. of Cond.	1
Approx LBS/MFT	360
Max O.D. (in)	0.600
Mil-Spec	M915E/21
Ampacity (Cond.) @ 50°	110
Metal Tubes	C
Nylon Tubes	4F
Cond. Material	Bare Copper
Insul. Material	Rubber
Jacket Material	Neoprene
Voltage	600
Mil-Spec	M915E/20
Ampacity (Cond.) @ 50°	121
Metal Tubes	B
Nylon Tubes	5A1
Cond. Material	Bare Copper
Insul. Material	Rubber
Jacket Material	Polyvinylchloride (PVC)
Voltage	600

Part Number: TRXF-105
MIL-C-915/21 (TRXF)

TRXF-105 Specifications: (subject to change without notice)

AWG Size	1/0
No. of Cond.	1
Approx LBS/MFT	460
Max O.D. (in)	0.680
Mil-Spec	M915E/21
Ampacity (Cond.) @ 50°	121
Metal Tubes	D
Nylon Tubes	4D
Cond. Material	Bare Copper
Insul. Material	Rubber
Jacket Material	Neoprene
Voltage	600

Part Number: TRXF-133
MIL-C-915/21 (TRXF)

TRXF-133 Specifications: (subject to change without notice)

AWG Size	2/0
No. of Cond.	1
Approx LBS/MFT	567
Max O.D. (in)	0.750
Mil-Spec	M915E/21
Ampacity (Cond.) @ 50°	141
Metal Tubes	D
Nylon Tubes	4E1
Cond. Material	Bare Copper
Insul. Material	Rubber
Jacket Material	Neoprene
Voltage	600

