

MIL-C-915/66 (MSPW)
MIL-C-915/66, M915/66 Shielded Circuits Cable
MSPW

MIL-C-915/66 Cable Approvals and Ratings:

Mil Spec: MIL-C-915E
Navy Spec: MSPW
Voltage Rating: 600 Volts
MIL-C-915/66 Construction:

Conductor: Tinned Copper
Insulation: Fluoropolymer
Jacket: Polyamide/Polyester Tape
Shield: Overall Tinned Copper Braid Shield
Combination construction
Unarmored with surface marking

MIL-C-915/66 Description:

Shielded Circuits Cable
Watertight Cable
Non-flexing Cable

Part Number	Approx LBS/MFT	Composite Construction	Max O.D. (in)
MSPW	1500	(16) 22 AWG Conductors, (18) 20 AWG Conductors and (25) 16 AWG Conductors	1.635

Part Number: MSPW
MIL-C-915/66 (MSPW)

MSPW Specifications: (subject to change without notice)
Approx LBS/MFT 1500
Composite Constru, (18) 20 AWG Conductors and (25) 16 AWG Conductors
Max O.D. (in) 1.635
Mil-Spec M915E/66
Metal Tubes R
Nylon Tubes 8A
Cond. Material Tinned Copper
Insul. Material Fluoropolymer
Jacket Material Polyamide/Polyester Tape
Shield Overall Braid Shield
Shield Material Tinned Copper Braid
Voltage 600

